

SPA 3000-6000TL-AU

- Scalable system configuration
- Supports retrofit & new system
- Smart bypass function ensures continues critical loads
- Max. 6kW backup power
- VPP interface ready



P O W E R
- I N G
T O M O R R O W

GROWATT

www.ginverter.com

Datasheet	SPA 3000TL-AU	SPA 3600TL-AU	SPA 4000TL-AU	SPA 4600TL-AU	SPA 5000TL-AU	SPA 6000TL-AU
AC Input /Output Data						
Rated output/input power	3000W	3680W	4000W	4600W	5000W	6000W
Rated output apparent power	3000VA	3680VA	4000VA	4600VA	5000VA	6000VA
Nominal AC voltage / (range)	230V / (180Vac-260Vac)					
AC grid frequency / (range)	50/60Hz / (45~55Hz/55~65Hz)					
Rated input/output current	13A/13A	16A/16A	17.3A/17.3A	20A/20A	21.7A/21.7A	26A/26A
Max. input/output current	16/16A	16/16A	22/22A	22/22A	27/27A	27/27A
Adjustable power factor	0.8leading...0.8lagging					
THDi	<3%					
AC grid connection type	Single phase					
Battery Data (DC)						
Battery voltage range	42~59V					
Minimum full load voltage	46V		48V			
Rated charging and discharging current	66/66A	75/75A	85/85A	96/96A	105/105A	125/125A
Continuous charging/ discharging power	3000W	3680W	4000W	4600W	5000W	6000W
Type of Battery	lithium /Lead-acid					
EPS Output Data						
Rated output apparent power	3000VA	3680VA	4000VA	4600VA	5000VA	6000VA
Nominal AC output voltage	230V					
Nominal AC output frequency	50/60Hz					
Rated output current	13A	16A	17.3A	20A	21.7A	26A
THDv	3%					
Switch time	≤15ms					
Efficiency						
Max. efficiency	97.20%	97.20%	97.30%	97.40%	97.50%	97.60%
Euro weighted efficiency	97%	97%	97.10%	97.10%	97.20%	97.20%
Protection Devices						
AC surge protection	Type III					
Insulation resistance monitoring	Yes					
AC short-circuit protection	Yes					
Ground fault monitoring	Yes					
Grid monitoring	Yes					
AFCI	Yes					
Anti-islanding protection	Yes					
Residual-current monitoring unit	Yes					
General Data						
Dimensions (W/H/D)	605/458/186mm					
Weight	32kg					
Operating temperature range	-25°C ... +60°C					
Nighttime power consumption	< 10 W					
Cooling	Natural					
Protection degree	IP66					
Altitude	3000m					
Relative humidity	0~100%					
AC connection	connector					
Battery connection	connector					
Display	LCD					
Interfaces	RS485/ USB /CAN/Wi-Fi/GPRS					
Warranty	10 years					
Place of production	Made in China					
CE, IEC62109, IEC61000, AS4777.2:2020, CEC						

* The maximum operation voltage is 560V, and if it exceeds 560V, the system will not work or stop working; The maximum input voltage is 600V, there is a risk of damage if the maximum value is exceeded.

* SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. Subject to change without notice.